



MATERIAL SAFETY DATA SHEET

COLD GAL PRIMER

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Zinc Protekt
 PRODUCT NO. CE54081301
 APPLICATION Speciality Paint
 SUPPLIER Master Distributors Pty Ltd
 ACN: 080 754 230
 31 Dunlop Road Mulgrave VIC 3170 Australia
 +613 9538-9200 Facsimile: +613 9538-9299
 sales@masterdistributors.com.au

EMERGENCY TELEPHONE Emergency telephone number: +61 3 9538 9200 (8.30am – 5.30pm EST, Monday - Friday)

2 HAZARDS IDENTIFICATION

Extremely flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION F+;R12. N;R50/53. R66, R67.

ENVIRONMENT

The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

PHYSICAL AND CHEMICAL HAZARDS

Pressurised container: Must not be exposed for temperatures above 50°C. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures.

HUMAN HEALTH

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ACETONE	200-662-2	67-64-1	10-30%	F;R11 Xi;R36 R66 R67
DIMETHYL ETHER	204-065-8	115-10-6	30-60%	F+;R12
SOLVENT NAPHTHA, LIGHT AROMATIC	265-199-0	64742-95-6	10-30%	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
XYLENE	215-535-7	1330-20-7	1-5%	R10 Xn;R20/21 Xi;R38
ZINC POWDER - ZINC DUST (STABILISED)		7440-66-6	30-60%	N;R50/53

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

Zinc Protekt

GENERAL INFORMATION

Move the exposed person to fresh air at once.

INHALATION

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

Immediately rinse mouth and provide fresh air. Do not induce vomiting. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash skin with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray, foam, dry powder or carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES

Use water spray to reduce vapours. Aerosol cans may explode in a fire. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.

UNUSUAL FIRE & EXPLOSION HAZARDS

Extremely flammable. Forms explosive mixtures with air. May explode in a fire. Vapours are heavier than air and may spread near ground to sources of ignition.

SPECIFIC HAZARDS

Pressurised container: Must not be exposed for temperatures above 50°C.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Provide ventilation and confine spill. Do not allow runoff to sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray mists. Do not spray on a naked flame or any incandescent material. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

STORAGE PRECAUTIONS

Extremely flammable. Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Zinc Protekt

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3
DIMETHYL ETHER	WEL	400 ppm	766 mg/m3	500 ppm	958 mg/m3
SOLVENT NAPHTHA, LIGHT AROMATIC	SUP		600 mg/m3		
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit. In case of inadequate ventilation use suitable respirator.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

HYGIENE MEASURES

When using do not eat, drink or smoke. Wash promptly if skin becomes wet or contaminated.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol		
COLOUR	Varying		
ODOUR	of solvents		
PHYSICAL DATA	Information given concerns the major ingredient. 23 Flammable gas.		
COMMENTS			
RELATIVE DENSITY	1.172	FLASH POINT (°C)	<-40°C
AUTO IGNITION	235 °C	FLAMMABILITY LIMIT -	0.7 % (v/v)
TEMPERATURE (°C)		LOWER(%)	
FLAMMABILITY LIMIT -	18.6 % (v/v)		
UPPER(%)			

10 STABILITY AND REACTIVITY

STABILITY

Highly volatile.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

11 TOXICOLOGICAL INFORMATION

SKIN CONTACT

Skin irritation is not anticipated when used normally. Repeated exposure may cause skin dryness or cracking.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

HEALTH WARNINGS

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Arrhythmia, (deviation from normal heart beat).

ROUTE OF ENTRY

Inhalation.

TARGET ORGANS

Central nervous system. Respiratory system, lungs.

MEDICAL SYMPTOMS

Narcotic effect. Vapours may cause drowsiness and dizziness.

Zinc Protekt

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment. The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment. Dangerous for the environment if discharged into watercourses. Do not allow to enter drains, sewers or watercourses.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Make sure containers are empty before discarding (explosion risk). Do not puncture or incinerate even when empty. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	2, 5F	UK ROAD PACK GR.	#
PROPER SHIPPING NAME	AEROSOLS	ADR CLASS	Class 2: Gases
UN NO. ROAD	1950	ADR LABEL NO.	2.1
ADR CLASS NO.	2, 5F	RID CLASS NO.	2, 5F
ADR PACK GROUP	#	UN NO. SEA	1950
CEFIC TEC(R) NO.	20G5F	IMDG PAGE NO.	2102
RID PACK GROUP	#	EMS	F-D, S-U
IMDG CLASS	2	UN NO. AIR	1950
IMDG PACK GR.	#	AIR SUB CLASS	2.1
MARINE POLLUTANT	No.		
AIR CLASS	2		
AIR PACK GR.	#		

15 REGULATORY INFORMATION

LABELLING



Extremely Flammable



Dangerous for the environment

RISK PHRASES

R12	Extremely flammable.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2	Keep out of the reach of children
S16	Keep away from sources of ignition - No smoking.

Zinc Protekt

S23	Do not breathe vapour/spray.
S24	Avoid contact with skin.
S29	Do not empty into drains.
S51	Use only in well-ventilated areas.
A1	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.

Poisons Schedule (Aust): S5 This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

16 OTHER INFORMATION

REVISION DATE 28-01-2008
 DATE 28th January 2007

RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Master Distributors Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.