

# Material Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Material Identification

**Product ID:** 400.0002351.076  
Product Name: 2351N RED OXIDE PRIMER 6U  
Product Use: Paint product.  
Print date: 15/Dec/2005  
Revision Date: 4th September 2009

### Company Identification

Master Distributors Plasti-kote  
31 Dunlop Road  
Mulgrave 3170 Victoria Australia  
Ph (03) 9538 9200  
Fax (03) 9538 9299  
sales@plasti-kote.com.au  
Emergency telephone number: 03 9538 9200 (8.30am - 5.30pm EST, Monday-Friday)

## 2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Common Name CAS-No.	Approx. Weight %	Chemical name
DIMETHYL KETONE 67-64-1	35 - 40	ACETONE
PROPANE 74-98-6	15 - 20	Propane
XYLENE (W/ ANTI-STATIC) 1330-20-7	5 - 10	Xylenes (o-, m-, p- isomers)
BUTANE 106-97-8	5 - 10	Butane
PROPRIETARY INERT	1 - 5	PROPRIETARY INERT
PROPRIETARY PIGMENT	1 - 5	PROPRIETARY PIGMENT
EXEMPT MINERAL SPIRITS 8052-41-3	1 - 5	Stoddard solvent
BARIUM METABORATE 13701-59-2	1 - 5	Barium metaborate
ISOBUTYL ACETATE 110-19-0	1 - 5	Isobutyl acetate
ETHYLBENZENE 100-41-4	1 - 5	Ethyl benzene

If this section is blank there are no hazardous components per OSHA guidelines.

## 3. HAZARDS IDENTIFICATION

### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

**Emergency Overview:**

This section not in use.

**This product contains ingredients that may contribute to the following potential acute health effects:****Inhalation Effects:**

Harmful if inhaled. May affect the brain, nervous system, or respiratory system, causing dizziness, headache, nausea or respiratory irritation.

**Eye Contact:**

Causes eye irritation.

**Skin Contact:**

May cause moderate skin irritation.

**Acute Ingestion:**

May be harmful if swallowed.

**Other Effects:**

May cause kidney damage. May cause liver damage.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Prolonged and/or repeated contact can result in skin irritation. May cause skin drying with prolonged exposure.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

## 4. FIRST AID MEASURES

**Inhalation:**

If affected by inhalation, move victim to fresh air. If symptoms persist, seek medical attention. If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

**Eye Contact:**

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

**Skin Contact:**

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean contaminated shoes.

**Ingestion:**

If swallowed, do not induce vomiting. Give large quantities of water. If available, give several glasses of milk. Never give anything by mouth to an unconscious person. Get medical attention immediately. If swallowed, get medical attention immediately.

**Medical conditions aggravated by exposure:** Any respiratory or skin condition.

## 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	-31° F ( -35° C) TCC/PM
Lower explosive limit:	2 %
Upper explosive limit:	13 %
Autoignition temperature:	Not available. ° F ( ° C)

Sensitivity to impact:  
Sensitivity to static discharge:

No.  
Subject to static discharge hazards. Please see bonding and grounding information in Section 7.  
See Section 10.

Hazardous combustion products:

**Unusual fire and explosion hazards:**

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers until disposed of in compliance with applicable regulations. Contains oxidizable materials.

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Use water spray to cool nearby containers and structures exposed to fire.

## 6. ACCIDENTAL RELEASE MEASURES

**Action to be taken if material is released or spilled:**

Ventilate area. Avoid breathing of vapors. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 5, "Unusual Fire and Explosion Hazards", for proper container and storage procedures. Remove sources of ignition. Remove with inert absorbent and non sparking tools. Avoid contact with eyes.

## 7. HANDLING AND STORAGE

**Precautions to be taken in handling and storage:**

Keep away from heat, sparks, and flames. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### Personal Protective Equipment

**Eye and face protection:**

Avoid contact with eyes. Wear chemical goggles if there is the possibility of contact or splashing in the eye.

**Skin protection:**

Appropriate chemical resistant gloves should be worn. To prevent skin contact wear protective clothing covering all exposed areas.

**Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

**Ventilation**

Required when spraying or applying in confined area. Ventilation equipment should be explosion proof. Eliminate ignition sources.

### Exposure Guidelines

### OSHA Permissible Exposure Limits (PEL's)

Common Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
DIMETHYL KETONE 67-64-1	35 - 40	2400 mg/m <sup>3</sup> 1000 ppm		
PROPANE 74-98-6	15 - 20	1800 mg/m <sup>3</sup> 1000 ppm		
XYLENE (W/ ANTI-STATIC) 1330-20-7	5 - 10	435 mg/m <sup>3</sup> 100 ppm		
PROPRIETARY INERT	1 - 5	5 mg/m <sup>3</sup> Respirable fraction. 15 mg/m <sup>3</sup> Total dust. Respirable fraction. Listed. Total dust. Listed.		
PROPRIETARY PIGMENT	1 - 5	10 mg/m <sup>3</sup> Fume.		
EXEMPT MINERAL SPIRITS 8052-41-3	1 - 5	2900 mg/m <sup>3</sup> 500 ppm		
BARIUM METABORATE 13701-59-2	1 - 5	0.5 mg/m <sup>3</sup> Ba		
ISOBUTYL ACETATE 110-19-0	1 - 5	700 mg/m <sup>3</sup> 150 ppm		
ETHYLBENZENE 100-41-4	1 - 5	435 mg/m <sup>3</sup> 100 ppm		

#### ACGIH Threshold Limit Value (TLV's)

Common Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
DIMETHYL KETONE 67-64-1	35 - 40	500 ppm	750 ppm		
PROPANE 74-98-6	15 - 20	1000 ppm			
XYLENE (W/ ANTI-STATIC) 1330-20-7	5 - 10	100 ppm	150 ppm		
BUTANE 106-97-8	5 - 10	1000 ppm			
PROPRIETARY INERT	1 - 5	2 mg/m <sup>3</sup> Respirable fraction. The value is for particulate matter containing no asbestos and <1% crystalline silica.			
PROPRIETARY PIGMENT	1 - 5	5 mg/m <sup>3</sup> Dust and fume. Fe			
EXEMPT MINERAL SPIRITS 8052-41-3	1 - 5	100 ppm			
BARIUM METABORATE 13701-59-2	1 - 5	0.5 mg/m <sup>3</sup> Ba			
ISOBUTYL ACETATE 110-19-0	1 - 5	150 ppm			
ETHYLBENZENE 100-41-4	1 - 5	100 ppm	125 ppm		

If this section is blank, no information is available.

## 9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	Liquid
pH:	Not determined.
Vapor pressure:	NOT DETERMINED mmHG @ 68° F ( 20° C)
Vapor density (air = 1.0):	4.8
Boiling point:	-42° F ( -41° C)
Solubility in water:	Not determined.
Coefficient of water/oil distribution:	Not determined.
Density (lbs per US gallon):	6.6
Specific Gravity	.79
Evaporation rate (butyl acetate = 1.0):	5.6

## 10. STABILITY AND REACTIVITY

Stability	Stable
Conditions to Avoid:	None known.
Incompatibility:	Strong oxidizers.
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. Metal oxide fumes.

**Sensitivity to static discharge:** Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

## 11. TOXICOLOGICAL INFORMATION

**Mutagens:**

**Teratogens:**

**Carcinogens:**

Contains ethylbenzene, which has been determined by NTP to be an animal carcinogen with no known relevance to humans. IARC has classified ethylbenzene as possibly carcinogenic to humans (2b) on the basis of sufficient evidence of carcinogenicity in laboratory animals but inadequate evidence of cancer in humans.

Common Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - limited human data	IARC Group 2b - sufficient animal data
ETHYLBENZENE 100-41-4	1 - 5			Monograph 77, 2000

Common Name CAS-No.	Approx. Weight %	NTP Known carcinogens	NTP Suspect carcinogens	NTP Evidence of carcinogenicity
ETHYLBENZENE 100-41-4	1 - 5			male rat-clear evidence; female rat-some evidence; male mice- some evidence; female mice-some evidence

Common Name CAS-No.	Approx. Weight %	OSHA Select carcinogens	OSHA Possible select carcinogens	ACGIH Carcinogens
ETHYLBENZENE 100-41-4	1 - 5			Group A3 Confirmed animal carcinogen with unknown relevance to humans.

If this section is blank, no information is available.

## 12. ECOLOGICAL DATA

Not available at this time.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

Proper Shipping Name: CONSUMER COMMODITY ORM-D  
UN ID Number: CONCOM

### 49 CFR Hazardous Material Regulations Parts 100-180

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity or "does not sustain combustion" exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

### International Air Transport Association:

Proper Shipping Name: AEROSOLS, FLAMMABLE  
Hazard Class: 2.1  
UN ID Number: UN1950

### International Maritime Organization:

Proper Shipping Name: AEROSOLS  
Hazard Class: 2  
UN ID Number: UN1950



## 15. REGULATORY INFORMATION

Common Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ IN LBS.
DIMETHYL KETONE 67-64-1	35 - 40			5000
XYLENE (W/ ANTI-STATIC) 1330-20-7	5 - 10		form R reporting required for 1.0% de minimis concentration	100
BARIUM METABORATE 13701-59-2	1 - 5		YES	
ISOBUTYL ACETATE 110-19-0	1 - 5			5000
ETHYLBENZENE 100-41-4	1 - 5		form R reporting required for 1.0% de minimis concentration	1000

**SARA 311/312 Hazard Class:**

Acute: Yes  
Chronic: Yes  
Flammability: Yes  
Reactivity: No  
Sudden Pressure: Yes

**U.S. STATE REGULATIONS:**

**Pennsylvania Right To Know:**

ETHYLBENZENE	100-41-4
BUTANE	106-97-8
ISOBUTYL ACETATE	110-19-0
PROPRIETARY PIGMENT	Trade Secret
EXEMPT MINERAL SPIRITS	8052-41-3
XYLENE (W/ ANTI-STATIC)	1330-20-7
PROPRIETARY INERT	Trade Secret
BARIUM METABORATE	13701-59-2
DIMETHYL KETONE	67-64-1
PROPANE	74-98-6

**Additional Non-Hazardous Materials**

**Poisons Schedule (Australia):**

**S5** All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

**Rule 66 status of product**

Photochemically reactive.

**INTERNATIONAL REGULATIONS - Chemical Inventories**

**TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

**16. OTHER INFORMATION**

**HMIS Codes**

**Health:** 2  
**Flammability:** 4  
**Reactivity:** 1  
**PPE:** X - See Section 8 for Personal Protective Equipment (PPE).

**Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

**DISCLAIMER:**

**Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Master Distributors Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for the product as sold, is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.**